

A1  
Amended

70 positioned on the motor shaft thereof, which engages a 23-toothed section gear 75 in an upward and downward direction, on one axis. The second motor 80 of the assembly 60 drives a 10-toothed fixed gear 85 positioned on the motor shaft thereof, which drives against an 82-toothed fixed gear 90 secured to a pivot shaft 100 with a snap ring 95. This preferably enables horizontal rotation of the housing 32 for 380-degrees on an axis that perpendicularly intersects the upward-downward axis of the gear 75 with respect to the pivot shaft 100. These motors 65, 80 are fixed with fasteners such as, screws, to a vertical pivot post 110 and a horizontal support assembly 120, respectively. The section gear is fixed with respect to the vertical pivot post 110, and the gear 90 is fixed with respect to the shaft 100.

---

**IN THE CLAIMS:**

Replace claim 1 with the following claim:

- A2
- B1
- 1.(AMENDED) A searchlight device comprising:
- a housing including a first end;
  - a window in the first end of said housing;
  - a lamp disposed within said housing so as to emit light through said window;
  - a shaft; and,
  - a positioning assembly secured within said housing, said positioning assembly including:
    - a first motor operable to rotate said housing in a first plane with respect to said shaft, and a
    - second motor operable to pivot said housing in a second plane with respect to said shaft.
-